


FLOOR SCREEN SERIES



Floor screen are special design for install on the floor and allow people step on it. By integrated with interactive system, it is able to make the contents interactive with the actions for the people who step above the screen.

Special features:

- High strength resistance and anti-skid materials, can afford up to 500kg/square meter weight;
- Seamless design, offer vivid and colorful viewing experience;
- Wide viewing angle, able using in stage;
- Interactive with people step on floor (optional interactive system required);
- Easy and quick maintenance by replacing failure cabinet separately;
- Special cooling system design ensures heat discharge quickly from the screen;



Model	FS-DF3	FS-DF4	FS-DF6	FS-DF8	FS-DF10
Pixel pitch (mm)	3.91	4.81	6.25	8.92	10
Pixel composition	1R1G1B				
LED Lamp	SMD1921	SMD2727	SMD3535	SMD3528	
Pixel Density (dot/m ²)	65410	43222	25600	12544	10000
Module Size	250 x 250 mm				320x320mm
Module Resolutions	64x64	52x52	40x40	28x28	32x32
Cabinet size (mm)	500 x 500 x 75				640x640x70
Cabinet Resolution	128 x 128	104 x 104	80 x 80	56 x 56	64 x 64
Cabinet Weight (kg)	11.5				14.5
IP rating	65	65	65	65	43
Brightness (CD/m ²)	1800	3000	3500	3500	800
Viewing Angle	120° / 120°				
Max Power Consumption	600W / m ²			550W / m ²	375W / m ²
Avg Power Consumption	240W / m ²			230W / m ²	150W / m ²
Refresh rate	≥1920 HZ				≥960HZ
Operating power	AC 100/220V 50/60HZ				
LED Operating life	100000 Hours @70% brightness				